



# Chain Actuators 200N

## WMX 804

This chain actuator is ideal for surface mounting for smoke and comfort ventilation. It is not appropriate for roof windows.

The electronics in this actuator can be programmed to suit specific requirements – i.e. pressure- and traction force, stroke, speed and sound level.

### Description

- to be used together with ±24V control units or control units with MotorLink™
- can be used together with Espagnolette WMB
- external safety edge can be connected directly to the actuator (actuator version 'E')
- synchronisation of up to four window actuators on a single window frame – no need for an external synchronisation module
- genuine position feedback and three speeds when using Motorlink™ Motor Controllers
- soft close
- the electronics in this actuator can be programmed to suit specific requirements i.e. pressure and traction force, stroke, speed and sound level
- built-in electronic load switch-off/end stop
- electronic actuator with micro controller
- the actuator has an integrated reverse function to ensure a prolonged life span of the window gaskets
- Easy mounting



### Technical Specifications

<b>Part No.</b>	08/WMX 804
<b>Chain Opening</b>	50 - 250mm in increments of 10mm
<b>Opening Speed</b>	7mm/s
<b>Pressure Force</b>	Max. 150N - dependent on the chain length
<b>Tractive Force</b>	Max. 200N
<b>Operating Voltage</b>	24 VDC (max. 10% ripple)
<b>Current consumption</b>	1A
<b>Size</b>	332 x 29 x 42mm (WxHxD)
<b>Colour</b>	Aluminium (RAL 9006) or white (RAL 9010)

### Diagram

