



Chain Actuators 200N

WMX 804

This chain actuator is ideal for surface mounting for smoke and comfort ventilation. It is not appropriate for roof windows.

The electronics in this actuator can be programmed to suit specific requirements – i.e. pressure- and traction force, stroke, speed and sound level.



Description

- to be used together with ±24V control units or control units with MotorLink™
- can be used together with Espagnolette WMB
- external safety edge can be connected directly to the actuator (actuator version 'E')
- synchronisation of up to four window actuators on a single window frame – no need for an external synchronisation module
- genuine position feedback and three speeds when using Motorlink™ Motor Controllers
- soft close
- the electronics in this actuator can be programmed to suit specific requirements i.e. pressure and traction force, stroke, speed and sound level
- built-in electronic load switch-off/end stop
- electronic actuator with micro controller
- the actuator has an integrated reverse function to ensure a prolonged life span of the window gaskets
- Easy mounting

Technical Specifications

Part No.	08/WMX 804
Chain Opening	50 - 250mm in increments of 10mm
Opening Speed	7mm/s
Pressure Force	Max. 150N - dependent on the chain length
Tractive Force	Max. 200N
Operating Voltage	24 VDC (max. 10% ripple)
Current consumption	1A
Size	332 x 29 x 42mm (WxHxD)
Colour	Aluminium (RAL 9006) or white (RAL 9010)

Diagram

