



Chain Actuators 200N

WMX 826

This chain actuator is ideal for surface mounting, for smoke and comfort ventilation.

To be used with top hung, bottom hung and casement windows.

Description

- to be used together with $\pm 24V$ control units or control units with MotorLink™
- can be used together with Espagnolette WMB
- external safety edge can be connected directly to the actuator (actuator version 'E')
- synchronisation of up to four window actuators on a single window frame – no need for an external synchronisation module
- genuine position feedback and three speeds when using MotorLink™ Motor Controller
- soft close
- the electronics in this actuator can be programmed to suit specific requirements i.e. pressure and traction force, stroke, speed and sound level
- built-in electronic load switch-off/end stop
- electronic actuator with micro controller
- the actuator has an integrated reverse function to ensure a prolonged life span of the window gaskets
- easy mounting



Technical Specifications

Part No	08/WMX 826
Pressure Force	See table below
Tractive Force	See table below
Nominal Voltage	24 VDC, max. 10% ripple
Power Consumption	1A
Size	487 x 30.5 x 42 mm (WxHxD)
Colour	Aluminium (RAL 9006) or White (RAL 910)

Diagram

IMPORTANT

Mount the actuator so the bottom of the housing (marked with a yellow label) faces towards the centre of the window

